



Smart Button

RTSS Smart Chain Smart Button is designed to work with a Smart Chain Node or Installation Node. Equipped with other basic environmental Sensors for additional reporting.

Designed to provide Inventory Awareness and Self Tests Functions to Insure system readiness at all times.

Programmable Alarm Group and Response Functions.

- Works in Loops with other Smart Chain Sensors or Buttons.
- Stainless Shield or Full Stainless Cases Available.
- Visual Indicator Available.
- Separate Normally Closed Contact to Interface to other control Systems.
- Allows for up to One Standard slave Button with NC contact

Unit Sensors	Specification	Features
<p>Single Locking Push Button (Twist to Unlock)</p> <p>Temperature: -40 °C to +120 °C</p> <p>Temperature Accuracy: ± 0.5 °C, 15 to +40 °C</p> <p>Humidity accuracy: ± 3.5% rH, 20 to +80% rH</p> <p>Absolute Pressure: 260 to 1260 hPa</p>	<p>Size: 100X100X100mm</p> <p>Supply: 24Vac</p> <p>Sensor Loops: One In/Out</p> <p>Outputs: 3 Relay, 1 TTL</p> <p>Wire Termination: Terminal</p> <p>Cable Penetration: Stainless Gland 1X10mm</p>	<p>Individual Electronic Serial Number</p> <p>Interrogation Status Response</p> <p>Automatic Inventory Control</p> <p>Environmental Sensor Options</p>



Seismec Marine Ltd
www.seismec.com
sales@seismec.com

Summit Resources AG
 Bahnhofstrasse 21, 6300 Zug, Switzerland
sales@summitresources.ch

©2019 All rights reserved.

